



PROCESS OPTION
DIM. OF "H"

0	$0.70^{+0.00}_{-0.35}$
1	$0.80^{+0.15}_{-0.10}$

SPECIFICATION
MATERIAL
 Insulator: Thermal Plastic UL94V-0
 Contacts: Copper Alloy
 CONTACT PLATING: Lgnore
 SHELL: Steel
 SHELL PLATING: 80u"~100u" Tin/Lead or 80u"~100u" Tin/Lead Free
 Min Base Copper: 40u" Min

ELECTRICAL
 Current Rating: 3 Amps Max.
 Contact Resistance: Ignore
 Insulation Resistance: 3000 Mohms Min @ 500 VDC
 Dielectric Withstanding Voltage: Lgnore

MECHANICAL
 Operating Temperature: -55°C To +105°C
 PART NO.

104 A X XX A 0 X A A X 3
 1 2 3 4 5 6 7 8 9 10 11

- | | |
|----------------------------------|---------------------|
| 1.SERIES NO. | 8.PROCESS OPTION: |
| 2.TYPE: A=Standard | A=Thru.Hole |
| 3.ENVIRONMENT PROTECTION | 9.PARTS OPTION: |
| MATERIAL: | A=Non Accessories |
| E=RoHS | 10.PROCESS OPTION: |
| 4.CONTACT NUMBER:
See Positin | 1=0.80±0.15 (LVF02) |
| 5.CONTACT TYPE: | 11.COLOR: 3=Black |
| A=Male (Metal Clip) | |
| 6.FILL IT WITH "O" | |
| 7.SHELL PLATING: | |
| P=Tin Plated+Dimple | |

POSITION	A	B	C	D	E	F	G
15M	16.92	25.00	30.8	2.29	1.14	19.2	7.04
26M	25.25	33.30	39.2	2.29	1.14	27.7	6.88
44M	38.96	47.10	53.1	2.29	1.14	41.1	6.88
62M	55.42	63.50	69.4	2.41	1.20	57.3	7.00

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2
SCALE: AS SHOWN	UNIT: mm
DRAWN: JOE	05/16/06
CHECKED:	/ /
APPROVED:	/ /
SIZE: A4	REV: 1



CHANT SINCERE CO., LTD
 TEL:886-02-86471251 FAX:886-02-86472962
 DRAWN NAME: D-SUB CRIMP HOUSING
 PRODUCT NO. 104AXXXA0XAAX3
 FILE NAME: 104AJXXA0XAAX3

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE
1			5		
2			6		
3			7		
4			8		