



PROCESS OPTION
DIM. OF "H"

0	0.70 ^{+0.00} _{-0.35}
1	0.80 ^{+0.15} _{-0.10}

SPECIFICATION

MATERIAL

Insulator: Thermal Plastic UL94V-0

Contacts: Copper Alloy

CONTACT PLATING: Ignore

SHELL: Steel

SHELL PLATING: 80u"~100u" Tin/Lead or 80u"~100u" Tin/Lead Free
Min Base Copper: 40u" Min

ELECTRICAL

Current Rating: 3 Amps Max.

Contact Resistance: Ignore

Insulation Resistance: 3000 Mohms Min @ 500 VDC

Dielectric Withstanding Voltage: Ignore

MECHANICAL

Operating Temperature: -55°C To +105°C

PART NO.

104 A X XX B 0 X A A X 3
1 2 3 4 5 6 7 8 9 10 11

1.SERIES NO.

2.TYPE: A=Standard

3.ENVIRONMENT PROTECTION

MATERIAL

E=RoHS

4.CONTACT NUMBER:

See Positin

5.CONTACT TYPE:

B=Female (Metal Clip)

6.FILL IT WITH "0"

7.SHELL PLATING:

T=Tin Plated

8.PROCESS OPTION:

A=Thru.Hole

9.PARTS OPTION:

A=Non Accessories

10.PROCESS OPTION:

1=0.80^{+0.15}_{-0.10} (LVF02)

11.COLOR: 3=Black

POSITION	A	B	C	D	E	F	G
15F	16.30	25.00	30.8	2.29	1.14	19.2	7.04
26F	24.60	33.30	39.2	2.29	1.14	27.7	6.88
44F	38.30	47.10	53.1	2.29	1.14	41.1	6.88
62F	54.80	63.50	69.4	2.41	1.20	57.3	7.00

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2

SCALE: AS SHOWN UNIT: mm

DRAWN JOE 05/17/06

CHECKED / /

APPROVED / /

SIZE A4 REV. G



CHANT SINCERE CO., LTD
TEL:886-02-6421251 FAX:886-02-6421962

DRAWN NAME:
D-SUB CRIMP HOUSING
CHANT SINCERE CO., LTD' LOGO

PRODUCT NO. 104AXXXBOXAAX3

FILE NAME: 104AJXXBOXAAX3

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE
1			5		
2			6		
3			7		
4			8		