



POSITION	A	B	C	D
9F	16.30	25.00	30.8	19.2
15F	24.60	33.30	39.2	27.7
19F	30.00	38.86	44.8	32.8
23F	35.30	44.30	50.3	38.3
25F	38.30	47.10	53.1	41.1
37F	54.80	63.50	69.4	57.3



**SPECIFICATION**

**MATERIAL**  
 Insulator: Thermal Plastic UL94V-0  
 Contacts: Copper Alloy  
 Shell: Steel  
 Rivet, Boardlock: Copper Alloy  
**CONTACT PLATING**  
 Underplated: 50u" ~100u" Nickel  
 Contact Area: 1u"~50u" Selective Gold  
 Solder Tails Area: 100u"~300u" Tin(Lead Free)  
**ELECTRICAL**  
 Operation Voltage: 250 VAC Max.  
 Current Rating: 3 Amps Max.  
 Contact Resistance: 15 mohms Max.  
 Insulation Resistance: 3000 Mohms Min @ 500 VDC  
 Dielectric Withstanding Voltage: 1000 VAC / Minute  
 Temperature Range: -55°C To +105°C  
**PART NO.**

201 A X XX X X X A A A X  
 1 2 3 4 5 6 7 8 9 10 11

- |   |   |
|---|---|
| 1.SERIES NO.  | 8.PROCESS OPTION                              |
| 2.TYPE: A=Standard  | A=Thru. Hole                                  |
| 3.GREEN OPTION:<br>E=RoHS                                     | 9.PARTS OPTION<br>A=Non Accessories           |
| 4.CONTACT NUMBER:<br>09 15 25 37                              | 10.CONTACT INSERTING OPTION<br>A=Fully Loaded |
| 5.CONTACT TYPE:<br>F=Female                                   | 11.INSULATOR COLOR<br>3=Black                 |
| 6.CONTACT AREA PLATING:<br>G=Gold Flash                       |   |
| 7.SHELL PLATING:<br>T=Tin Plated Over 50u" Min. Copper Plated |   |

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. ±5 0. ±0.5 .0 ±0.3 .00 ±0.2	SCALE: AS SHOWN UNIT: mm		 <b>CHANT SINCERE CO., LTD</b> TEL:886-02-86471251 FAX:886-02-86472962
CHECKED / /	APPROVED / /	SIZE A4	REV. L
REV.			DESCRIPTION
DATE			FILE NAME: 201AKXXFXXAAAX