



P.C.B LAYOUT

POSITION	A	B	C	D
09	16.34	24.99	30.81	11.08
15	24.76	33.32	39.14	19.39
25	38.33	47.04	53.04	33.24
37	54.89	63.50	69.32	49.86

MATERIALS AND FINISH
 SHELL : STEEL MATERIAL, NICKEL FINISHED
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 CONTACT MATERIAL: BRASS
 CONTACT FINISH : FULL GOLD FLASHED
 GROUNDING BRACKET : BRASS MATERIAL, TIN FINISHED

ELECTRICAL CHARACTERISTICS
 CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

PART NO. $\frac{206}{1} \frac{A}{2} \frac{X}{3} \frac{XX}{4} \frac{F}{5} \frac{X}{6} \frac{X}{7} \frac{B}{8} \frac{B}{9} \frac{C}{10} \frac{3}{11}$

- | | |
|---|--|
| 1.SERIES NO. | 8.PROCESS OPTION: |
| 2.TYPE: A=Standard | B=Rivet W/Boardlock |
| 3.GREEN OPTION:
E=RoHS(Bright) | 9.PARTS OPTION:
B=4#40 Thread Rivet |
| 4.CONTACT NUMBER:
09 15 25 37 | 10.PARTS DIMENSION
C=Fixed Hex-Screws(4.8*11.8) |
| 5.CONTACT TYPE:
F=Female | 11.INSULATOR:
3=Black |
| 6.CONTACT PLATING:
G=Gold Flash Over All | |
| 7.SHELL PLATING:
T=Tin Plated | |

For SIP

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANG.	±5°	
0.	±0.5	CHANT SINCERE CO.,LTD TEL:886-02-86471251 FAX:886-02-86472962
.0	±0.3	
.00	±0.2	
SCALE: AS SHOWN	UNIT: mm	
DRAWN CHERRY	01/19/16	DRAWN NAME: D-SUB Right Angle 0.402"Footprint
CHECKED	/ /	PRODUCT NO. 206AXXXFXXBBC3
APPROVED	/ /	FILE NAME: 206AFXXFXXBBC3(H03)

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	C