



P.C.B LAYOUT

No. of Contact	A±0.20	B±0.20	C±0.20	D
09	16.90	24.99	30.81	11.08
15	26.38	33.32	39.14	19.39
25	39.94	47.04	53.04	33.24
37	56.43	63.50	69.32	49.86

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED
 DIMPLES ON PLUG ONLY
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS
 FILLED, UL 94V-0 RATED, BLACK COLOR
 CONTACT MATERIAL : BRASS
 CONTACT FINISH : SELECTIVE GOLD FLASH
 GROUNDING BRACKET : BRASS MATERIAL, TIN FINISHED
 JACK SCREWS : STEEL MATERIAL , NICKEL FINISHED
 WITH #4-40 THREADED ASSEMBLED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

PART NO.

206 A X XX M X X B B C 3
 1 2 3 4 5 6 7 8 9 10 11

- 1.SERIES NO.
- 2.TYPE: A=Standard
- 3.GREEN OPTION:
E=RoHS(Bright)
- 4.CONTACT NUMBER:
09 15 25 37
- 5.CONTACT TYPE:
M=Male
- 6.CONTACT PLATING:
G=Gold Flash Over All
- 7.SHELL PLATING:
P=Tin Plated+Dimple
- 8.PROCESS OPTION:
B=Rivet W/Boardlock
- 9.PARTS OPTION:
B=4#40 Thread Rivet
- 10.PARTS DIMENSION
C=Fixed Hex-Screws(4.8*11.8)
- 11.INSULATOR:
3=Black

For SIP

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2

SCALE: AS SHOWN	UNIT: mm
DRAWN CHERRY	01/19/16
CHECKED	/ /
APPROVED	/ /



CHANT SINCERE CO., LTD
 TEL:886-02-86471251 FAX:886-02-86472962

DRAWN NAME:
D-SUB Right Angle 0.402"Footprint

PRODUCT NO. 206AXXXMXXBBC3

FILE NAME: 206AFXMXXBBC3(H03)

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	C