

P.C.B LAYOUT  
TOLERANCES: ±0.05mm

No. of Contact	A ±0.25 ±.010	B ±0.13 ±.005	C ±0.38 ±.015	D
09	16.92 .666	24.99 .984	30.81 1.213	11.08 .436
15	25.25 .994	33.32 1.312	39.14 1.541	19.39 .763
25	38.96 1.534	47.04 1.852	53.04 2.088	33.24 1.310
37	55.42 2.182	63.50 2.500	69.32 2.729	49.86 1.963

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED

DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR

CONTACT MATERIAL : BRASS

CONTACT FINISH : SELECTIVE GOLD FLASH

GROUNDING BRACKET : BRASS MATERIAL, TIN FINISHED

JACK SCREWS : BRASS MATERIAL , NICKEL FINISHED WITH #4-40 THREADED ASSEMBLED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS

CONTACT RESISTANCE : 30 MILLIOHMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.

INSULATION RESISTANCE : 5000 MEGAOHMS MIN.

TEMPERATURE RATING : -55°C ~ +105°C

PART NO.

206 A X XX M X X A A C 3  
1 2 3 4 5 6 7 8 9 10 11

1.SERIES NO.

2.TYPE: A=Standard

3.GREEN OPTION:

E=RoHS

4.CONTACT NUMBER:

09 15 25 37

5.CONTACT TYPE:

M=Male

6.CONTACT PLATING:

G=Gold Flash

7.SHELL PLATING:

P=Tin Plated+Dimple

8.PROCESS OPTION:

A=Fixed W/Boardlock

9.PARTS OPTION:


A=Non Rived

10.PARTS DIMENSION

C=Fixed Hex-Screws(4.8\*11.8)

11.INSULATOR:

3=Black

UNLESS OTHERWISE SPECIFIED TOLERANCE		 <b>CHANT SINCERE CO., LTD</b> TEL:886-02-86471251 FAX:886-02-86472962
ANG.	±2° .00 ±0.25	
SCALE:	AS SHOWN	UNIT: mm
DRAWN	Vicky	07/01/11
CHECKED	/ /	DRAWN NAME: D-SUB Right Angle 0.402"Footprint
APPROVED	/ /	PRODUCT NO. 206AXXXMXXAAC3
REV.	A	FILE NAME: 206AXXXMXXAAC3(H03)

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME:
1			A4	A	206AXXXMXXAAC3(H03)