



RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: $\pm 0.05\text{mm}$

SPECIFICATION

MATERIAL

Insulator: PBT, Glass Fill Reinforced UL94V-0

Contacts: Brass (Standard)

Shell: Steel

Rivet, Boardlock: Copper Alloy

CONTACT PLATING

Gold Flash

ELECTRICAL

Operation Voltage: 250 VAC Max.

Current Rating: 3 Amps Max.

Contact Resistance: 15 mohms Max.

Insulation Resistance: 3000 Mohms Min. @ 500 VDC

Dielectric Withstanding Voltage: 1000 VAC / minute

Operating Temperature: -55°C to $+105^{\circ}\text{C}$

PART NO.

208 A E XX M X X A A A X
1 2 3 4 5 6 7 8 9 10 11

1. SERIES NO.

2. TYPE: A=Standard

3. ENVIRONMENT PROTECTION

MATERIAL.

E=RoHS

4. CONTACT NUMBER:

09 15 25 37

5. CONTACT TYPE:

M=Male

6. CONTACT AREA PLATING:

G=Machine Pin Gold Flash

7. SHELL PLATING:

P=Tin+Dimple

8. PROCESS OPTION:

A=Standard W/O Bracket

9. PARTS OPTION:

A=Non Accessories

10. PARTS DIMENSION

A=Fully Loaded

11. INSULATOR:

3=Black

POSITION	A	B	C
9M	16.92	25.00	30.8
15M	25.25	33.30	39.2
19M	30.60	38.86	44.8
23M	35.90	44.30	50.3
25M	38.96	47.10	53.1
37M	55.42	63.50	69.4

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	$\pm 5^{\circ}$
0.	± 0.5
.0	± 0.3
.00	± 0.2
SCALE: AS SHOWN	UNIT: mm
DRAWN RITA	06/15/07
CHECKED	/ /
APPROVED	/ /
SIZE A4	REV. A



CHANT SINCERE CO., LTD

TEL: 886-02-86471251 FAX: 886-02-86472962

DRAWN NAME: D-SUB PCB RIGHT ANGLE MALE

PRODUCT NO. 208AEXXMXXAAAX

FILE NAME: 208AEXXMXXAAAX(83)

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		