

Note:

1.Material:

- 1.1 Front Insulator: P.B.T UL 94-V0 rated.
- 1.2 Back Insulator: PA66 UL 94-V0 rated.
- 1.3 Contact:Ignore
- 1.4 Shell: Cold rolled steel,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30mΩMax.
- 2.4 Insulation resistance: 1000Ω/Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u~30u".
- 3.2 Shell: Nickel,tin or Zinc plated

PART NO.

210 A E XX M O X A A O 3
 1 2 3 4 5 6 7 8 9 10 11

1.SERIES NO.

2.TYPE:

A=Standard

3.ENVIRONMENT PROTECTION

E=RoHS

4.CONTACT NUMBER:

09,15,25,37

5.CONTACT TYPE:

M=Male

6.FILL IT WITH"O"

7.SHELL PLATING:

P=Tin+Dimple

8.PROCESS OPTION:

A=Thru.Hole

9.PARTS OPTION:

A=Non Accessories


10.FILL IT WITH"O"

11.INSULATOR:

3=Black

No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish
4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Tin/Nickel/Zinc Plated
3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Tin/Nickel/Zinc Plated
2	Contact	37	Brass	T=0.20mm	Gold Flashed
1	Back Housing	1	PA66	UL 94-V0	Black
	Front Housing	1	P.B.T	UL 94-V0	Black

POSITION	A	B	C
9M	16.92	25.00	30.80
15M	25.25	33.32	39.20
25M	38.96	47.04	53.05
37M	55.42	63.50	69.40

UNLESS OTHERWISE SPECIFIED TOLERANCE		 CHANT SINCERE CO.,LTD TEL:886-02-86471251 FAX:886-02-86472962
ANG. ±1° .x ±0.3 .xx ±0.20 .xxx ±0.100		
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME: D-SUB CRIMP HOUSING CHANT SINCERE CO.LTD PRODUCT NO. 210AEXXMOXAA03 FILE NAME: 210AEXXMOXAA03(H)
DRAWN CHERRY	12/04/07	
CHECKED	/ /	
APPROVED	/ /	
REV. B	SIZE A4	

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		