



RECOMMENDED P.C.BOARD HOLE DIMM

For SIP

MATERIAL

Insulator : Nylon 66+GF,UL94V-0

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Voltage Rating : 250V AC Maximum

Insulation Resistance : 1000M Ω Min.

Contact Resistance : 10m Ω Max

PART NO.

311 A E XX M A T B2 R _____ 4 D 1
 1 2 3 4 5 6 7 8 9 10 III 2

- 1.SERIES NO.
- 2.TYPE D=DIP
- 3.GREEN OPTION E=RoHS
- 4.CONTACT NO. 02~ 20
- 5.CONTACT TYPE M=MALE A=SINGLE ROW
- 6.ROW TYPE T=TIN PLATED
- 7.CONTACT PLATING
- 8.PITCH OPTION B2=2.5MM
- 9.CONTACT OPTION R=RIGHT ANGLE
- 10.PROCESS OPTION 4=TYPE 4
- 11.PACKAGE OPTION D=BAG
- 12.INSULATOR COLOR I=WHITE

Poles	Dimensions		Poles	Dimensions	
	A	B		A	B
			11	25.00	30.00
2	2.50	7.50	12	27.50	32.50
3	5.00	10.00	13	30.00	35.00
4	7.50	12.50	14	32.50	37.50
5	10.00	15.00	15	35.00	40.00
6	12.50	17.50	16	37.50	42.50
7	15.00	20.00	17	40.00	45.00
8	17.50	22.50	18	42.50	47.50
9	20.00	25.00	19	45.00	50.00
10	22.50	27.50	20	47.50	52.50

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. = $\pm 3^\circ$.0 = $\pm .30$.00 = $\pm .20$		 CHANT SINCERE CO.,LTD TEL:886-02-86471251 FAX:886-02-86472962	
SCALE: AS SHOWN	UNIT: MM		
DRAWN PEARL	03/14/2016	DRAWN NAME: WAFER Pitch 2.5mm	
CHECKED		PRODUCT NO. 311AEXXMATB2R3D1	
APPROVED		FILE NAME: 311AEXXMATB2R3D1(P)	

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			A4	X1	311AEXXMATB2R3D1(P)