



Recommended P.C.B Layout

For SIP

MATERIAL
Contact Pin : Brass

SPECIFICATION

Current Rate : 9 AMP
Voltage Rating : 600V(R.M.S.)
Insulation Resistance : 1000MΩMin. at DC 500V
Contact Resistance : 30mΩMax. at DC 100mA

PART NO.

3 1 1 A E XX M B T D I R 4 D 9
1 2 3 4 5 6 7 8 9 10 11 12

- 1.SERIES NO.
- 2.TYPE D=DIP
- 3.GREEN OPTION
E=RoHS
- 4.CONTACT NO.
02~24
- 5.CONTACT TYPE
M=MALE
B=DUAL ROW
- 7.CONTACT PLATING
T=TIN PLATED (80~120u")

- 8.PITCH OPTION
D1=4.2MM
- 9.CONTACT OPTION
R=RIGHT ANGLE
- 10.PROCESS OPTION
4=TYPE 2
- 11.PACKAGE OPTION
D=BAG
- 12.INSULATOR COLOR
9=TRANSPARENCY

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG.=±3° .0 =±.30 .00 =±.20		 CHANT SINCERE CO.,LTD TEL:886-02-86471251 FAX:886-02-86472962	
SCALE: AS SHOWN	UNIT: MM		
DRAWN PEARL	01/13/2017	DRAWN NAME: WAFER Pitch 4.2mm	
CHECKED		PRODUCT NO. 311AEXXMBTD1R4D9	
APPROVED		FILE NAME: 311AEXXMBTD1R4D9(P)	
REV.	DESCRIPTION	DATE	SIZE A4 REV. X2