



PIN NO	DIMENSION MM (IN)	
	A	B
2P	0.8(.031)	3.8(.150)
3P	1.6(.062)	4.6(.181)
4P	2.4(.094)	5.4(.213)
5P	3.2(.126)	6.2(.244)
6P	4.0(.157)	7.0(.276)
7P	4.8(.189)	7.8(.307)
8P	5.6(.220)	8.6(.339)
9P	6.4(.252)	9.4(.370)
10P	7.2(.283)	10.2(.402)
11P	8.0(.315)	11.0(.433)
12P	8.8(.346)	11.8(.465)
13P	9.6(.378)	12.6(.496)
14P	10.4(.409)	13.4(.528)
15P	11.2(.441)	14.2(.559)
16P	12.0(.472)	15.0(.591)
17P	12.8(.504)	15.8(.622)
18P	13.6(.535)	16.6(.654)
19P	14.4(.567)	17.4(.685)
20P	15.2(.598)	18.2(.717)

1. MATERIAL
 1.1: HOUSING:1.PA46 or 2.LCP UL 94-V0
 1.2: CONTACT: PHOSPHOR BRONZE
 1.3: LEG:PHOSPHOR BRONZE.
2. PLATING
 2.1: CONTACT: TIN OVER NICKEL
 2.2: LEG: TIN OVER NICKEL
3. RATING:
 3.1: CURRENT RATING:1A AC, DC
 3.2: VOLTAGE RATING:50V AC, DC
 3.3 OPERATING TEMPERATURE: -25° ~+85°

PART NO. **311 D E X X M A T 0 1 R O C 1**
 1 2 3 4 5 6 7 8 9 10 11 12

- 1.SERIES NO.
 2.TYPE D=SMT
 3.GREEN OPTION
 E=RoHS
 4.CONTACT NO.
 02~20
 5.CONTACT TYPE
 M=Male
 6.ROW TYPE
 A=Single Row
 7.CONTACT PLATING
 T=Tin Plated
- 8.PITCH OPTION
 01=0.8mm
 9.CONTACT OPTION
 R=Right Angle
 10.PROCESS OPTION
 0=NON Distribution
 11.PACKAGE OPTION
 C=Tape & Reel
 12.INSULATOR COLOR
 1=White

UNLESS OTHERWISE SPECIFIED TOLERANCE	
.0	±0.20
.00	±0.15
.000	±0.10



CHANT SINCERE CO., LTD
 TEL:886-02-86471251 FAX:886-02-86472962

SCALE: AS SHOWN	UNIT: mm
DRAWN PEARL	10/14/13
CHECKED	/ /
APPROVED	/ /

DRAWN NAME:
 WAFER SMT Pitch 0.8mm
 PRODUCT NO. 311DEXXMAT01ROC1

REV.	DESCRIPTION	DATE	SIZE A4	REV. X1	FILE NAME: 311DEXXMAT01ROC1(W3)
------	-------------	------	---------	---------	---------------------------------