



CIRCUITS	Dim A	Dim B	Dim C
2	2.00	7.90	4.60
3	4.00	9.90	6.60
4	6.00	11.98	8.60
5	8.00	13.98	10.60
6	10.00	15.98	12.60
7	12.00	17.98	14.60
8	14.00	19.98	16.60
9	16.00	21.98	18.60
10	18.00	23.98	20.60
11	20.00	25.98	22.60
12	22.00	27.98	24.60
13	24.00	29.98	26.60
14	26.00	32.98	28.60
15	28.00	33.98	30.60
16	30.00	35.98	32.60

Available: 2~16pins
 Mate with 312A(B10X)
 Insulator: High Temperature Thermoplastic UL
 Color: Natural
 Conductor: Brass/Tin plated

PART NO.

311 D E XX M A T B1 R 1 D 4
 1 2 3 4 5 6 7 8 9 10 11 12

- 1.SERIES NO.
- 2.TYPE D=SMT
- 3.GREEN OPTION E=RoHS
- 4.CONTACT NO. 02~16
- 5.CONTACT TYPE M=Male
- 6.ROW TYPE A=Single Row
- 7.CONTACT PLATING T=Tin Plated

- 8.PITCH OPTION B1=2.0mm
- 9.CONTACT OPTION R=Right Angle
- 10.PROCESS OPTION 1=TYPE 1
- 11.PACKAGE OPTION D=Bag
- 12.INSULATOR COLOR 4=Gray

UNLESS OTHERWISE SPECIFIED TOLERANCE
 X' ±2
 .0 ±0.30
 .00 ±0.20
 .000 ±0.10

SCALE: AS SHOWN UNIT: mm

DRAWN PEARL 10/14/13

CHECKED / /

APPROVED / /

SIZE A4 REV. X1



CHANT SINCERE CO., LTD
 TEL:886-02-86471251 FAX:886-02-86472962

DRAWN NAME: WAFER SMT Pitch 2.0mm

PRODUCT NO. 311DEXXMATB1R1D4

FILE NAME: 311DEXXMATB1R1D4(W3)

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		