



CIRCUITS	Dim A	Dim B	Dim C
2	2.00	7.90	4.60
3	4.00	9.90	6.60
4	6.00	11.98	8.60
5	8.00	13.98	10.60
6	10.00	15.98	12.60
7	12.00	17.98	14.60
8	14.00	19.98	16.60
9	16.00	21.98	18.60
10	18.00	23.98	20.60
11	20.00	25.98	22.60
12	22.00	27.98	24.60
13	24.00	29.98	26.60
14	26.00	32.98	28.60
15	28.00	33.98	30.60
16	30.00	35.98	32.60

Available: 2~16pins
 Mate with 312A(B10X)
 Insulator: High Temperature Thermoplastic UL 94V-0
 Color: Natural
 Conductor: Brass/Tin plated

- PART NO. 311 D E XX M A T B1 S 1 D 4
 1 2 3 4 5 6 7 8 9 10 11 12
- 1.SERIES NO.
 - 2.TYPE D=SMT
 - 3.GREEN OPTION E=RoHS
 - 4.CONTACT NO. 02~16
 - 5.CONTACT TYPE M=Male
 - 6.ROW TYPE A=Single Row
 - 7.CONTACT PLATING T=Tin Plated
 - 8.PITCH OPTION B1=2.0mm
 - 9.CONTACT OPTION S=Strait
 - 10.PROCESS OPTION 1=TYPE 1
 - 11.PACKAGE OPTION D=Bag
 - 12.INSULATOR COLOR 4=Gray

UNLESS OTHERWISE SPECIFIED TOLERANCE	
X'	±2
.0	±0.30
.00	±0.20
.000	±0.10
SCALE: AS SHOWN	UNIT: mm
DRAWN PEARL	10/14/13
CHECKED	/ /
APPROVED	/ /

OXOC

CHANT SINCERE CO.,LTD
 TEL:886-02-86471251 FAX:886-02-86472962

DRAWN NAME: WAFER SMT Pitch 2.0mm

PRODUCT NO. 311DEXXMATB1S1D4

FILE NAME: 311DEXXMATB1S1D4(W3)

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	X1