

Dimensional Information

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	3.0	9.65	4	9.0	15.65	6	15.0	21.65
3	6.0	12.65	5	12.0	18.65	7	18.0	24.65

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
8	21.0	27.65	10	27.0	33.65	12	33.0	39.65
9	24.0	30.65	11	30.0	36.65			

Features:

- 2 ~ 12 circuits available
- Material: LCP
- Tin-plated brass pin
- Mates with 312A(C101)Male housing


Specification:

- Current rating: 5A AC, DC
- Voltage rating: 250V AC, DC
- Contact resistance: 10mΩ Max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -25°C ~ 85°C

PART NO.

311 D E XX M A T C1 S X D 3
 1 2 3 4 5 6 7 8 9 10 11 12

- | | |
|-------------------|-----------------------|
| 1.SERIES NO. | 8.PITCH OPTION |
| 2.TYPE D=SMT | C1=3.0mm |
| 3.GREEN OPTION | 9.CONTACT OPTION |
| E=RoHS | S=Strait |
| 4.CONTACT NO. | 10.PROCESS OPTION |
| 02~12 | 2=TYPE 1(W/SMT Pad) |
| 5.CONTACT TYPE | 3=TYPE 1(W/Boardlock) |
| M=Male | 11.PACKAGE OPTION |
| 6.ROW TYPE | D=Bag |
| A=Single Row | 12.INSULATOR COLOR |
| 7.CONTACT PLATING | 3=Black |
| T=Tin Plated | |



Shown with disposable cap

UNLESS OTHERWISE SPECIFIED TOLERANCE		
.0	±0.25	
.00	±0.15	CHANT SINCERE CO., LTD TEL:886-02-86471251 FAX:886-02-86472962
.000	±0.05	
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME:
DRAWN PEARL	08/11/2016	WAFER SMT Pitch 3.0mm
CHECKED		PRODUCT NO. 311DEXXMATC1SXD3
APPROVED		FILE NAME: 311DEXXMATC1S2D3(W3)

REV.	DESCRIPTION	DATE	SIZE	REV.
			A4	X2