

**Features:**

- Material: P.B.T UL 94V-0
- Accepts 313A(A200)Male terminal
- Mates with 312A(A200)Male housing

**Specification:**

- Current rating: 1A AC, DC
- Voltage rating: 100V AC, DC
- Insulation resistance: 100MΩ Min.
- Withstand voltage: 500V AC/minute
- Temperature range: -25°C ~ 85°C


PART NO.

312 A E XX F A 0 A2 0 0 D 1  
 1 2 3 4 5 6 7 8 9 10 11 12

- |                    |                    |
|--------------------|--------------------|
| 1.SERIES NO.       | 8.PITCH OPTION     |
| 2.TYPE A=Standard  | A2=1.25mm          |
| 3.GREEN OPTION     | 9.FILL IT WITH "0" |
| E=RoHS             | 10.PROCESS OPTION  |
| 4.CONTACT NO.      | 0=NON Distribution |
| 02~10              | 11.PACKAGE OPTION  |
| 5.CONTACT TYPE     | D=Bag              |
| F=Female           | 12.INSULATOR COLOR |
| 6.ROW TYPE         | 1=White            |
| A=Single Row       |                    |
| 7.FILL IT WITH "0" |                    |

**Dimensional Information ( mm )**

POSITION	Dim. A	Dim. B	POSITION	Dim. A	Dim. B	POSITION	Dim. A	Dim. B
2	1.25	4.25	6	6.25	9.25	10	11.25	14.25
3	2.50	5.50	7	7.50	10.50			
4	3.75	6.75	8	8.75	11.75			
5	5.00	8.00	9	10.00	13.00			

UNLESS OTHERWISE SPECIFIED TOLERANCE		 <b>CHANT SINCERE CO.,LTD</b> TEL:886-02-86471251 FAX:886-02-86472962
.0	±0.25	
.00	±0.15	
.000	±0.05	
SCALE: AS SHOWN	UNIT: mm	
DRAWN PEARL	10/04/13	DRAWN NAME:
CHECKED	/ /	Wafer Housing Pitch
APPROVED	/ /	1.25mm
		PRODUCT No. 312AEXXFA0A200D1
		FILE NAME: 312AEXXFA0A200D1(W3)

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	X1