

Features:

- Material: Brass
- Finished: Tin-plated (Lead free)
- Used in 312A(C202~05) series housing
- Wire range: AWG #18 ~ #22
- Thickness: 0.25mm
- Q'ty/Reel: 7000 PCS


Specification:

- Current rating: 5A AC, DC
- Voltage rating: 250V AC, DC
- Contact resistance: 10mΩ max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -25°C ~ 85°C

PART NO.

313 A E 00 F P T C2 0 2 X 0
1 2 3 4 5 6 7 8 9 101112

- | | |
|---------------------|---------------------|
| 1.SERIES NO. | 8.PITCH OPTION |
| 2.TYPE A=Crimp | C2=3.96mm |
| 3.GREEN OPTION | 9.FILL IT WITH "0" |
| E=RoHS | 10.PROCESS OPTION |
| 4.FILL IT WITH "00" | 2=TYPE 2 |
| 5.CONTACT TYPE | 11.PACKAGE OPTION |
| F=Female | C=Tape Reel |
| 6.MATERIAL OPTION | D=Bag |
| P=Brass | 12.FILL IT WITH "0" |
| 7.CONTACT PLATING | |
| T=Tin Plated | |

UNLESS OTHERWISE SPECIFIED TOLERANCE		 CHANT SINCERE CO.,LTD TEL:886-02-86471251 FAX:886-02-86472962
.0	±0.40	
.00	±0.25	
.000	±0.08	
SCALE: AS SHOWN	UNIT: mm	
DRAWN PEARL	09/18/13	DRAWN NAME: .156"(3.96mm) Crimp Terminal
CHECKED	/ /	
APPROVED	/ /	PRODUCT NO. 313AE00FPTC202X0
REV.		FILE NAME: 313AE00FPTC202X0(W3)

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		