

Features:

- Material: Phosphor bronze
- Finished: Tin-plated
- Used in 312A(A200)Male series housing
- Wire range: AWG #28 ~ #32



Specifications:

- Current rating: 1A (0.8A for #32 AWG)
- Voltage rating: 125V
- Contact resistance: 20mΩ max.
- Dielectric withstanding voltage: 250V AC/minute
- Ambient temperature range: -40°C ~ 85°C

PART NO.

313 A E 00 F S T A2 0 0 X 0
 1 2 3 4 5 6 7 8 9 10 11 12

- | | |
|---------------------|---------------------|
| 1.SERIES NO. | 8.PITCH OPTION |
| 2.TYPE A=Crimp | A2=1.25mm |
| 3.GREEN OPTION | 9.FILL IT WITH "0" |
| E=RoHS | 10.PROCESS OPTION |
| 4.FILL IT WITH "00" | O=NON Distribution |
| 5.CONTACT TYPE | 11.PACKAGE OPTION |
| F=Female | C=Tape Reel |
| 6.MATERIAL OPTION | D=Bag |
| S=Phosphor Bronze | 12.FILL IT WITH "0" |
| 7.CONTACT PLATING | |
| T=Tin Plated | |

UNLESS OTHERWISE SPECIFIED TOLERANCE		 CHANT SINCERE CO., LTD TEL:886-02-86471251 FAX:886-02-86472962	
.0	±0.25		
.00	±0.15		
.000	±0.05		
SCALE: AS SHOWN	UNIT: mm	DRAWN NAME: .049*(1.25mm) Pitch Wire-to-Board Crimp Terminal PRODUCT NO. 313AE00FSTA200X0 FILE NAME: 313AE00FSTA200X0(W3)	
DRAWN PEARL	09/18/13		
CHECKED	/ /		
APPROVED	/ /		
REV.	DESCRIPTION	DATE	 SIZE A4 REV. X1