

RoHS
compliant

SPECIFICATION
MATERIAL AND FINISH:
1. INSULATOR: THERMAL PLASTIC UL94V-0, WHITE
2. CONTACTS: COPPER ALLOY
PLATING: UNDERPLATE: 50u"~150u" NI
CONTACT AREA: 5u"~15u" SELECTIVE AU
SOLDER TAILS AREA: 100u" MIN. SN(MATTE)
3. MOUNT EAR: COPPER ALLOY

Chant Sincere Co., Ltd.
17APR2024
Research & Development Dept.

**RECOMMENDED P.C.B. LAYOUT
TOLERANCE : ± 0.05**

UNLESS OTHERWISE SPECIFIED TOLERANCE:

PIN TYPE	INTERFACE DIM. L	PIN NO.
POWER	5.00 mm	1,13,38,50
GENERAL	4.25 mm	ALL OTHERS PINS
DETECT	3.50 mm	25,26

ASSEMBLY WITH MYLAR DRAWING

ITEM	NEW P/N	OLD P/N	CONTACT PLATING	PART OPTION
2	57522010010	752DF50MCT1214A1	15u" AU	W/O MYLAR
1				

DRAWN: XINGRU_LAI 02 Apr 2024
CHECKED: PEARL_HUNG 02 Apr 2024
APPROVED: PEARL_HUNG 02 Apr 2024

TITLE: CFA TYPE 2 (W/GROUNDING EXT.)
STANDARD TYPE (STANDOFF 2.2)

PART NO. 57522010010

CODE: GA CUSTOMER:

SCALE: AS SHOWN UNIT: mm

Cmk Cpk

CHANT SINCERE CO., LTD

ZONE REVISION DESCRIPTION DATE

1 2 3 4 5 6 7 8 9 10