



RECOMMENDED P.C.B LAYOUT  
TOLERANCES:  $\pm 0.05\text{mm}$

Current Rating: 1 Amps  
 Insulator Resistance: 1000 Megohms min  
 Contact Resistance: 20m ohms max.  
 Dielectric Withstanding: AC 500 V  
 Operating Temperature:  $-40^{\circ} \sim +85^{\circ}\text{C}$   
 Max Processing Temp: 230°C for 60 seconds  
 Max Processing Temp: 260°C for 10 seconds  
 Contact Material: Copper Alloy  
 Insulator Material: Polyester, UL 94V-0  
 Standard: L.C.P.

Finish: Gold Plated  
 Standard: Gold Flash all over

PART NO.  $\frac{708}{1} \frac{D}{2} \frac{X}{3} \frac{XXX}{4} \frac{P}{5} \frac{XC}{6} \frac{1}{7} \frac{0}{8} \frac{3}{9}$

- |                          |                      |
|--------------------------|----------------------|
| 1. SERIES NO.            | 7. INSULATOR HEIGHT  |
| 2. TYPE:                 | C=5.4mm              |
| D=SMT                    | 8. PROCESS OPTION:   |
| 3. GREEN OPTION:         | 1=W/Peg              |
| E=RoHS                   | 9. PROCESS OPTION:   |
| 4. CONTACT NUMBER:       | 0=W/O Pick Pad+Tube  |
| 006 ~ 080                | 10. INSULATOR COLOR: |
| 5. CONTACT TYPE:         | 3=Black              |
| P=Non Distribution       |                      |
| 6. CONTACT AREA PLATING: |                      |
| G=Gold Flash             |                      |

UNLESS OTHERWISE SPECIFIED TOLERANCE			
.0	$\pm 0.2$		
.00	$\pm 0.2$	<b>CHANT SINCERE CO., LTD</b> TEL: 886-02-86471251 FAX: 886-02-86472962	
.000	$\pm 0.2$	SCALE: AS SHOWN	UNIT: mm
DRAWN PEARL		08/29/08	DRAWN NAME:
CHECKED		/ /	BOX HEADER SMT TYPE (PITCH: 1.27x1.27mm)
APPROVED		/ /	PRODUCT NO. 708DXXXXPXC103
REV. A		SIZE A4	FILE NAME: 708DFXXXXPXC103(C6)

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		