



Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute

PART NO.

714 D X XX R X B S 03 X B 3
 1 2 3 4 5 6 7 8 9 101112

- 1.SERIES NO.
- 2.TYPE: D=SMT
- 3.GREEN OPTION:
E=RoHS(Bright Plated)
- 4.CONTACT NUMBER:
04~98
- 5.CONTACT TYPE:
R=Male(PA6T)
- 6.CONTACT AREA PLATING:
G=Gold Flash
- 7.ROW TYPE:
B=Dual Row
- 8.CONTACT OPTION:
S=Straight
- 9.CONTACT LENGTH:
03=03 TYPE
- 10.CONTACT OPTION:
0=W/O PAD,W/O PEG(Fully Loaded)
1=W/PAD,W/O PEG(Fully Loaded)
- 11.PACKAGE OPTION:
B=Tube
3=Black

POLES	DIM E	POLES	DIM E
		26	31.75
2	1.27	27	33.02
3	2.54	28	34.29
4	3.81	29	35.56
5	5.08	30	36.83
6	6.35	31	38.10
7	7.62	32	39.37
8	8.89	33	40.64
9	10.16	34	41.91
10	11.43	35	43.18
11	12.70	36	44.45
12	13.97	37	45.72
13	15.24	38	46.99
14	16.51	39	48.26
15	17.78	40	49.53
16	19.05	41	50.80
17	20.32	42	52.07
18	21.59	43	53.34
19	22.86	44	54.61
20	24.13	45	55.88
21	25.40	46	57.15
22	26.67	47	58.42
23	27.94	48	59.69
24	29.21	49	60.96
25	30.48	50	62.23

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. = ±3°
 .0 = ±.30
 .00 = ±.20



CHANT SINCERE CO., LTD
 TEL: 886-02-86471251 FAX: 886-02-86472962

SCALE: AS SHOWN UNIT: mm
 DRAWN PEARL 07/11/2016
 CHECKED
 APPROVED

DRAWN NAME:
Pin Header SMT Straight
(Pitch: 1.27*1.27mm)
 PRODUCT NO. 714DXXRXBS03XB3

For SIP

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME:
			A4	X1	714DFXXRXBS03XB3(P)