



WIRING DIAGRAM(22AWG)

- 1 BROWN
- 2 WHITE
- 3 BLUE
- 4 BLACK
- 5 GRAY
- 6 SHELL

SPECIFICATION
ELECTRICAL CHARACTERISTIC:
1. CURRENT RATING(40°C): 4A
2. VOLTAGE RATING: 250V AC/DC

ENVIRONMENTAL :
1. TEMPERATURE RANGE: -25°C TO +85°C

8	CABLE	UL2661#22(17/016 TA)AE 5C OD: 5.7±0.2mm, JACKET: PVC BLACK
7	EPOXY	NAEFUMI0 7391-38 A:B= 3:1
6	RUBBER BOOT	SILICON RUBBER 70°
5	PLASTIC BODY	PA66(6401G6) GF30%, RATED UL94V-0
4	MALE MIDDLE HOLDER	BRASS(C3604-EH) 50u" NI MIN.
3	MALE FRONT METAL BODY	BRASS(C3604-EH) 50u" NI MIN.
2	CONTACT	BRASS(C3604-EH) OVER 50u" NI MIN. GOLD FLASH
1	CONNECTOR	M12 A-CODE 5PIN MALE CABLE END
ITEM	PART	DESCRIPTION

2					
1	1490402001A	CW04A5AAAB05E1M0	1000mm	A-CODE	
ITEM	NEW P/N	OLD P/N	L (LENGTH)	CODE	NOTE
UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. ±2° 0. ±0.50 0. ±0.30 .00 ±0.20			SIP Cmk Cpk	 CHANT SINCERE CO.,LTD	
SCALE: AS SHOWN			UNIT: mm		
DRAWN: KEVIN_ZHENG			16 Jan 2025	TITLE: PDR- M12 A-CODE 5PIN MALE WITH CABLE OPEN END	
CHECKED: PEARL_HUNG			16 Jan 2025		
APPROVED: PEARL_HUNG			16 Jan 2025	PART NO.	1490402XXXX
			SIZE A4 SHEET 1/1	REV. A	CODE: CG CUSTOMER:

	A	ECN-2501062(KIRA)NEW P/N	14JAN2025
	X1	ECR-184119(TOPHER)	25APR2018
ZONE	REVISION	DESCRIPTION	DATE
1	2	3	4
5	6	7	8
9	10		