

P1

P2

400 (-0/+20)

REMARK:

Finished cable must 100% test passed.
There is no short circuit, open circuit and temporary interruption.

Testing requirements:

- 1. Insulation resistance: 10 M
- 2. Conduction resistance: 3
- Reted voltage: 300V

②	IDC 40P PH=2.0mm 有鼻(高鼻) 二件式 黑色 602AE40PSAB003	2PCS
①	UL2651 28AWG 40C PH:1.0MM 灰色红边	1PCS
NO.	DESCRIPTION	Q'TY

CONN	WIER LIST										
P1	1	2	3	4	5	36	37	38	39	40
P2	1	2	3	4	5	36	37	38	39	40


PART NO. **D M M 40 1 B53 E 40C**

SERIES NO. **D** M M 40 1 B53 E 40C

D=FLAT CABLE
CONNECTOR OPTION
M=602A IDC SOCKET
CONNECTOR OPTION
M=602A IDC SOCKET
PIN TYPE
40=40P/40P

LENGTH:
40C=400mm
GREEN OPTION:
E=RoHS
SPEC. TYPE.
COLOR TYPE.
1=BLACK/BLACK

RPS CODE: 0CBFU0064A

UNLESS OTHERWISE SPECIFIED TOLERANCE		 CHANT SINCERE CO., LTD TEL:886-02-86471251 FAX:886-02-86472962
0. ±1.0	.0 ±0.5	
.00 ±0.3		
SCALE: AS SHOWN	UNIT: mm	
DRAWN PEARL	10/19/2016	DRAWN NAME:
CHECKED	/ /	IDC 2.0 40P TO 40P L=400mm
APPROVED	/ /	PRODUCT NO. DMM401B53E40C
		FILE NAME: DMM401B53E40C(Z)

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		

For SIP



SIZE A4 REV. X2